

# Polyester Lidding Films & Heat Sealable Overwrap

PressSense®, in conjunction with Mylar® Specialty Films offers the broadest range of Mylar® Lidding and Mylar Heat Sealable overwrap polyester films. Mylar® products are engineered to meet the most demanding applications. PressSense film experts will assist in identifying the ideal solution along with custom converting, quick-turn around and inventory stocking programs.

## Lidding Film Features:

- Dual Ovenable - microwave and conventional oven safe
- Shred Resistant
- Superior strength for skeleton wind
- Seals to variety of trays
- Self-Venting during cooking
- Excellent hot tack
- Low seal initiation temperature
- Strong seals to maintain adhesion through contamination, refrigeration & freezing applications
- Anti-fog treatment available for refrigerated applications
- Corona Treated or chemical treated for bonding of inks, adhesives and laminations
- FDA compliant

## Heat Sealable Overwrap Features:

- Dual Ovenable - microwave and conventional oven
- Coextruded, one side amorphous, heat sealable
- FDA compliant

## Applications:

- |                                     |  |
|-------------------------------------|--|
| • Fresh Cut Produce                 | • Bakery Items                                       |
| • Refrigerated Foods & Frozen Foods | • Burritos   |
| • Institutional Meals               | • Breakfast Sandwiches                               |
| • Shelf Stable Product              | • Electronic Packaging                               |
| • Salads                            | • Medical Device Packaging                           |
| • Fruit Cups*                       | • Laminated Structures                               |
| • Soups*                            | • Applications for Lidding or Heat Sealable Overwrap |
| • Salsa*                            |  |

\* Application for lidding only

**PressSense® Films** is a premier precision converter and distributor of polyester and polypropylene film in North America. We focus on building collaborative relationships with our customers by providing outstanding customer service, key technical support and exceptional product performance.



## Contact Us:

For more information about our extensive line of films, contact your **PressSense Films** sales specialist to find the best solution for your applications. Call us at 800-443-1420 or visit [presssense.com](http://presssense.com).

## PressSense®, Inc.

14503 Gougar Rd., Unit 1  
Lockport, IL 60491

**Web:** [presssense.com](http://presssense.com)

**Fax:** 630-257-3583

**Email:** [Sales@PressSense.com](mailto:Sales@PressSense.com)

# Mylar® Lidding & Heat Sealable Overwrap - Product Finder

Which Mylar®  
Polyester Film  
is right for your  
product?  
Find the perfect  
film for your  
application.

## Contact Us:

For more information  
about our extensive  
line of films, contact  
your **PressSense  
Films** sales specialist  
to find the best  
solution for your  
applications. Call us  
at 800-443-1420 or  
visit [presssense.com](http://presssense.com).

## PressSense®, Inc.

14503 Gougar Rd., Unit 1  
Lockport, IL 60491

Phone: 800-443-1420

Web: [presssense.com](http://presssense.com)

Email: [Sales@PressSense.com](mailto:Sales@PressSense.com)

MYLAR LIDDING & OVERWRAP FILM TYPE	FILM THICKNESS (GAUGE)	Treatments		Tray types						Peel Strength				Usability	
		Anti-Fog	Corona Treated	APET, CPET, PETG	Aluminum Foil	PVC, PVdC, PAPER	PS, HIPS	PP	PE	Easy	Firm	Strong	Very Strong	Ovenable - Microwave & Conventional	Frozen & Refrigerated
CLT-F	50, 100			X	X	X					X			X	X
HF01AP	75	X		X	X	X					X				X
HF01AT	100	X	X	X	X	X					X				X
HF02APSR	100	X		X	X	X						X			X
HF01APSR	100	X		X	X	X					X				X
HF43AP	75	X		X	X	X	X	X	X			X			X
HF43AT	100	X	X	X	X	X	X	X	X			X			X
OL	50, 75, 100, 150			X	X	X				X				X	X
OLT	50, 75, 100, 150		X	X	X	X				X				X	X
OLAF	50, 100, 150	X		X	X	X					X			X	X
OLAFT	50, 100, 150	X	X	X	X	X					X			X	X
OL2	50, 75, 100			X	X	X					X			X	X
OL2T	50, 75, 100		X	X	X	X					X			X	X
OL3	50, 100			X	X	X						X		X	X
OL3T	50, 100		X	X	X	X						X		X	X
OL12	50, 100, 150			X	X	X						X		X	X
OL12AF	50, 100, 150	X		X	X	X						X		X	X
OL12T	50, 100, 150		X	X	X	X						X		X	X
OL13	50, 100, 150			X	X	X							X	X	X
OL13T	50, 100, 150		X	X	X	X							X	X	X
OL13AF	50, 100, 150	X		X	X	X							X	X	X
OL13AT	50, 100, 150	X	X	X	X	X							X	X	X
OWF*	48, 80, 120													X	X
OWF2*	60													X	X
RL31	50, 75, 100			X	X	X	X		X	X				X	X
RL32	50, 75, 100, 150			X	X	X	X		X		X			X	X
RL32T	50, 75, 100, 150		X	X	X	X	X		X		X			X	X
RL33	50, 100, 150			X	X	X	X		X			X		X	X
RL42	50, 75, 100, 150			X	X	X	X	X	X		X			X	X
RL42AF	50, 75, 100	X		X	X	X	X	X	X		X			X	X
RL43	50, 100			X	X	X	X	X	X			X		X	X
RL43AF	100	X		X	X	X	X	X	X			X		X	X
RL44T	100		X	X	X	X	X	X	X				X	X	X
RL51	50, 75, 100			X	X	X	X		X	X				X	X
RL52	50, 100, 150			X	X	X	X		X		X			X	X
RL52T	50, 100, 150		X	X	X	X	X		X		X			X	X
RL53	50, 100, 150			X	X	X	X		X			X		X	X
RL53T	50, 100, 150		X	X	X	X	X		X			X		X	X

\*Heat Sealable Overwrap

All information and recommendations contained herein are intended as a guide; purchaser should independently determine the best suitability of materials purchased for their testing and individual applications. **PressSense® Films** makes no guarantee of results and assumes no obligation or liability in connection with this information.