

# Biaxially Oriented Polypropylene (BOPP)

PressSense® provides a broad portfolio of polypropylene film types and thicknesses providing solutions for your critical applications. As a premier converter of plastic films, PressSense® offers custom converting, technical support, quick-turn and inventory stocking programs.

## Features:

- Heat Sealable and Non-Sealable
- Specific types promote maximum shelf life with oxygen and moisture barrier\*
- Specific types offer the highest clarity and gloss\*
- Can be used in laminations or single webs
- Specific types offers Anti-Fog properties \*
- Treatments for bonding of inks, adhesives and laminations
- Clear, White, Matte, Metalized
- FDA compliant

\* refer to product technical data sheet for specifications

## Applications:

- Runs on VFFS and HFFS equipment
- Flexible Packaging
- Box Overwrap
- Print and/or Laminations
- Confectionery
- Bags
- Bakery
- Snacks
- Frozen Foods
- Cosmetics
- Perfumes

- Tea
- Reamwrap
- Folding Carton/Bag Window
- Labels
- Overlamine
- Ice Cream/Popsicles
- Spices
- Produce
- Vitamins



## Contact Us:

For more information about our extensive line of films, contact your **PressSense Films** sales specialist to find the best solution for your applications. Call us at 800-443-1420 or visit [presssense.com](http://presssense.com).

**PressSense® Films** is a premier precision converter and distributor of polyester and polypropylene film in North America. We focus on building collaborative relationships with our customers by providing outstanding customer service, key technical support and exceptional product performance.

**PressSense®, Inc.**  
14503 Gougar Rd., Unit 1  
Lockport, IL 60491  
**Web:** [presssense.com](http://presssense.com)  
**Fax:** 630-257-3583  
**Email:** [Sales@PressSense.com](mailto:Sales@PressSense.com)

# Polypropylene Products - Sealable & Non-Sealable

Select the polypropylene product that fits your application.

POLYPROPYLENE FILM TYPE	THICKNESS	PRODUCT SPECIFICATIONS
DuraKlear AF	1.18, 1.37, 1.55	Clear, 1 side anti-fog, sealable 1 side, high energy treated 1 side
DuraKlear HS	.59, .69, .79, .97, 1.16, 1.37, 1.55, 1.95	Clear, 2 side sealable, 1 side treated
DuraKlear NS	.48, .74, .97, 1.16, 1.95	Clear, non-sealable, 1 side high energy treated, 1 side corona treated, slip modified
DuraKlear RC	.80, 1.00, 1.20, 1.40, 1.60, 2.00, 2.40	Clear, 2 side acrylic, 2 side heat sealable
DuraKlear RD	1.00, 1.25, 1.40, 1.60, 2.10	Clear, 1 side PVDC, 1 side acrylic, 2 side sealable
DuraMatte HS	.69, 1.16	Matte 1 side, 1 side sealable, 1 side high energy treated, slip modified
DuraMatte NS	.68, .97, 1.16	Matte 1 side, non-sealable, 1 side high energy treated
DuraMatte PCT2M	.48, .52, .60, .72, .80	Matte 1 side, non-sealable, 2 side treated
DuraMET HS	.79, .97, 1.16	Metalized 1 side, 1 side sealable, 1 side high energy treated
DuraWhite CHS	1.38, 1.69	White, cavitated, 2 side sealable, 1 side treated
DuraWhite IPL	1.00, 1.15, 1.52, 2.17	White, cavitated, non-sealable, 2 side treated
DuraWhite NCHS	.89, 1.08	White, non-cavitated, 2 side sealable, 1 side treated
DuraWhite PW	3.18	White, cavitated, 1 side high energy treated, 1 side corona treated

*Additional polypropylene film types and thicknesses available upon request.*

*All information and recommendations contained herein are intended as a guide; purchaser should independently determine the best suitability of materials purchased for their testing and individual applications. **PressSense® Films** makes no guarantee of results and assumes no obligation or liability in connection with this information.*