

A Polypropylene based film with a removable low tack adhesive. The adhesive has the ability to be cleanly removed for up to 6 months indoors. Available in White.

## End Uses

Appliances  
Counter Mats  
P.O.P. Displays  
Window Decals  
Identification Tags  
Labels  
Greeting Cards  
Signs  
Automotive P.O.P.

## Characteristics

Applies easily to most non-porous surfaces. Prints UV and conventional offset, screen or flexographic process. PressSense EZKling can be die or guillotine cut.

## Application Method

EZKling should be applied using dry method only. To apply, remove the liner and apply the adhesive side to your surface. A squeegee may be used to remove air bubbles.

## General Capabilities

Typical Properties	White PP
Minimum Application Temperature -F°	+40° Degrees Fahrenheit
Adhesive Service Temperature Range -F°	-40° to 180°
Thickness	3.2-3.4
Liner	90# Stay Flat
Adhesive Thickness	.8 to 1 Mil
Adhesion to Glass	12 to 24 oz/in.
Liner Thickness	6.7 mils
Shelf Life	6 month shelf life when stored at 70° and 50% RH.

## Recommendations

Completely test for your specific application.

Typical properties should be referenced as a general guide, not as a guarantee. Testing should be completed on material based on individual customer systems, efficiencies, temperatures and applications as properties can change based on customer production methods.